

SAFESPEAR | LIFT

Chain Blocks - 3m Lift

WITH OVERLOAD PROTECTION

0.5-10 tonne capacity range.

3m standard lift with load chain.

Hand-chain operated lifting mechanism.

Built-in overload protection.



Safespear branded product illustration.

Range & technical specifications

Safespear product ID	Capacity (t)	Lift (m)	Falls	Weight (kg)
SS-CB-0.5T-3M	0.5	3	1	11
SS-CB-01T-3M	1	3	1	12.5
SS-CB-02T-3M	2	3	1	19.5
SS-CB-03T-3M	3	3	2	29
SS-CB-05T-3M	5	3	2	41.3
SS-CB-10T-3M	10	3	4	78.5

Capacity (t)	Chain (mm)	Headroom (mm)	A / B / C (mm)
0.5	5 x 15	345	132 / 148 / 28
1	6 x 18	376	151 / 172 / 32
2	8 x 24	470	175 / 210 / 36
3	8 x 24	565	176 / 230 / 46
5	9 x 30	688	189 / 280 / 46
10	9 x 30	765	189 / 463 / 57

Overload-protected manual lifting range. Safespear IDs are ordering references.

Final supplied model, specifications, AS 1418.2 conformity and documentation confirmed on enquiry.

Follow the supplied nameplate and operating instructions. Never exceed rated capacity.