

SAFESPEAR | LIFT

Lever Hoists

WITH OVERLOAD PROTECTION

0.8-9 tonne capacity range.

Manual lifting and load positioning.

1.5m standard lift with load chain.

Compact all-steel body and overload clutch.



Safespear branded product illustration.

Range & technical specifications

Safespear product ID	Capacity (t)	Lift (m)	Falls	Weight (kg)
SS-LH-0.8T-1.5M	0.8	1.5	1	7
SS-LH-1.6T-1.5M	1.6	1.5	1	11
SS-LH-3.2T-1.5M	3.2	1.5	1	21
SS-LH-6.3T-1.5M	6.3	1.5	2	31
SS-LH-09T-1.5M	9	1.5	3	47

Capacity (t)	Chain (mm)	Headroom (mm)	Handle (mm)	Test load (kN)
0.8	6 x 18	325	280	11.3
1.6	8 x 24	380	410	22.5
3.2	10 x 30	480	410	45
6.3	10 x 30	620	410	90
9	10 x 30	700	410	135

Overload-protected manual lifting range. Safespear IDs are ordering references.

Final supplied model, specifications, AS 1418.2 conformity and documentation confirmed on enquiry.

Follow the supplied nameplate and operating instructions. Never exceed rated capacity.