

SAFESPEAR

THE SHARP END OF SAFETY



16A EX-TEMPORARY POWER EXTENSION LEAD

Our 16A Ex-Power Extension Leads are IECEx certified for the temporary installation of electrical maintenance equipment and are designed to take a beating. Rated for Extra Hard Usage, the highly flexible H07RN-F cables are extremely high on impact, cutting, abrasion, oils, and most industrial chemicals. Their flexible jackets allow for easy installation and routing of the cable.

APPLICATIONS



LNG
Refineries



Offshore
Platforms



Chemical
Plants



Shutdowns
& Turnarounds

Key Features

- > ATEX/IECEx-certified for gas- and dust atmospheres (Zone 1, 2, 21 and 22)
- > Compact, flexible and portable Configuration
- > Effortless plug-in operation
- > High degree of protection IP 66, even when plugged
- > Glove Operation
- > Variety of cable sizes & lengths
- > All-embracing IECEx Certificate of Conformity

Technical Specifications

Zone Rating	Zone 1, 2, 21 & 22
IECEx Certificate of Conformity	IECEx UL 13.0062X
Rated Current	16A
Voltage	200-250V
Frequency	50/60 Hz
Degree of protection accd. to EN 60529	IP66
Connecting Cable	H07RN-F
Plug Options	CEAG, STAHL
Socket Options	CEAG, STAHL
Length	20m or 30m



www.safespear.com.au