

SAFESPEAR

THE SHARP END OF SAFETY



63A EX-POWER EXTENSION LEAD & TROLLEY

Our 63A Ex-Power Extension Leads are IECEx certified for the temporary installation of electrical maintenance equipment such as HVAC Units and other electrical apparatus in explosive/hazardous environments, the rugged trolley mounted design provides ultra-portability to help eliminate the need for any manual handling.

APPLICATIONS



LNG
Refineries



Offshore
Platforms



Chemical
Plants



Shutdowns
& Turnarounds

Key Features

- > ATEX/IECEx-certified for gas - and dust atmospheres (Zone 1, 2, 21 and 22)
- > Compact, flexible and portable Configuration
- > Effortless plug-in operation
- > High degree of protection IP 66, even when plugged
- > Glove Operation
- > Lockable against unauthorised use

Technical Specifications

Zone Rating	Zone 1, 2, 21 & 22
Rated Current	63A
Voltage	380-480V
Permissible Ambient Temperature	- 20 °C up to +55 °C
Frequency	50/60 Hz
Pin Arrangement	3P+N+E / 3P+E
Degree of protection accd. to EN 60529	IP66
Connecting Cable	H07RN-F
Plug Options	CEAG, STAHL
Socket Options	CEAG, STAHL
Length	30m or customised length's available



www.safespear.com.au