

Our Ex-portable splitter box is a compact and user-friendly energy distribution for safe use in zones 1 and 2. Developed to high quality standards only components from Eaton are used to ensure the reliability for the product. This smart solution allows to connect easily to portable equipment such as portable lighting, blowers etc.

APPLICATIONS



LNG Refineri



Offshore Platform



Chemica Plants



Key Features

- > ATEX/IECEx-certified for gas- and dust atmospheres (Zone 1, 2, 21 and 22)
- > Compact, flexible and portable Configuration
- > High mechanical, chemical and thermal resistance
- > High degree of protection IP 66, even when plugged
- > AC3 rated breaking capacity
- > Allows the use of various portable type ex-equipment (lights & fans)
- > All-embracing IECEx Certificate of Conformity



Technical Specifications

Zone Rating	Zone 1, 2, 21 & 22
IECEx Certificate of Conformity	IECEx BKI 06.0007
Output	4 x 3-Pole 16A
Rated Voltage	200-250V
Permissible Ambient Tempreture	- 20 °C up to +55 °C
Frequency	50/60 Hz
Degree of protection accd. to EN 60529	IP66
Connecting Cable	H07RN-F
Plug Options	CEAG, STAHL
Socket Options	CEAG, STAHL
Length	15m or 25m
Weight	13kg

